

Groundwater Flow Model for Evaluation of Hydrologic Effects of the San Joaquin River Restoration

Presented by Jon Traum, P.E.

Preliminary Findings

Overview

- * San Joaquin River Restoration Program (SJRRP)
- * Model development
- * Model calibration
- * Model results
- * Model applications

SJRRP Overview


- * Restoration Goal

- * To restore and maintain fish populations in “good condition” in the main stem of the San Joaquin River below Friant Dam to the confluence of the Merced River, including naturally reproducing and self-sustaining populations of salmon and other fish.


- * Water Management Goal

- * To reduce or avoid adverse water supply impacts to all of the Friant Division long-term contractors that may result from the Interim Flows and Restoration Flows provided for in the Settlement.


San Joaquin River, Restoration Releases from Friant Dam, as Reported by Exhibit B of the Stipulation of Settlement^{1,2}



¹ - NRDC v Rodgers, Stipulation of Settlement, CIV NO. S-88-1658 - LKK/GGH, Exhibit B. September 13, 2006
² - Hydrographs reflect assumptions about seepage losses and tributary inflows which are specified in the settlement



SJRRP Seepage Management Issues








Model Purpose

- * Predict change in seepage due to SJRRP flows
- * Determine areas likely to developing high water-table conditions
- * Evaluate effectiveness of potential management actions
- * Provide quantitative information about groundwater flow system

Model Overview

- * Developed using MODFLOW Farm Process
- * 1,300-square-mile area
- * 150-mile reach of the San Joaquin River
- * April 1961 – September 2003
- * Monthly stress periods
- * Simulated features include
 - * 3-D aquifer sediment texture
 - * Surface-water flow and stream-aquifer interaction
 - * Agricultural supply and demand




Model Area and Model Grid


Model Hydrogeology

- * Well log data grouped into classes
 - * Gravel
 - * Sand
 - * Muddy Sand
 - * Clay
- * 3-D dataset developed using Transition-Probability Geostatistical Software (TPROGS)
- * Dataset mapped onto model grid using HUF package

Combined Domains San Joaquin River Restoration





Combined Domains San Joaquin River Restoration



Agricultural Supply and Demand

- * Simulated using USGS Farm Process
- * Farm Process simulated components
 - * Precipitation
 - * Surface water delivery
 - * Groundwater pumping
 - * Plant uptake of shallow groundwater
 - * Plant evapotranspiration
 - * Precipitation and irrigation runoff
 - * Deep percolation
 - * And lots more!
- * Farm Process data input using 28 subregions






Simulated Subregions


Model Calibration

- * 55 CCID monitoring wells
- * 78 DWR/USGS database wells
- * 19 stream flow gages
- * 81 model parameters
- * Semi-automated calibration using PEST




Calibration Well 19 - CCID140

CCID South




Calibration Well 105 - 10S12E13L001M

CCID South




Calibration Well 122 - 07S08E23R001M


CCID North



Calibration Well 63 - 14S16E04A001M


Mendota






Model Results – Water Use Budget

- * Inflows (Supply)
 - * Precipitation
 - * Surface Water Delivery
 - * Agricultural Groundwater Pumping
 - * Groundwater Uptake by Plants
- * Outflows (Demand)
 - * Crop Consumptive Use
 - * Runoff to Streams
 - * Percolation to Groundwater





Simulated Water Demand

Model Results – Groundwater Budget


- * Outflows

- * Municipal Groundwater Pumping
- * Agricultural Groundwater Pumping

- * Inflows


- * Net Percolation to Groundwater
- * Net Stream Seepage to Groundwater
- * Net Subsurface Boundary Flow


- * $\text{Change in Storage} = \text{Inflows} - \text{Outflows}$




Model Result Maps

- * Groundwater elevation
- * Depth to groundwater
- * Groundwater & surface water interaction







Depth to Groundwater



Fall 1991 Simulated (ft)



Stream-aquifer interaction – 1961 to 2003 average (acre-ft/month per cell)



Stream-aquifer interaction – February 1984 (acre-ft/month per cell)


Preliminary Findings

Model Application


Impacts of SJRRP Flows

- * Baseline
 - * No SJRRP flows
 - * Historical conditions and hydrology
- * Several scenarios with different SJRRP flow routing and timings

Groundwater Level Cross Section at Mariposa Bypass – January 1997




Groundwater Level Time Series near Sand Slough




Potential Seepage Mitigation Alternatives

- * Install slurry walls
- * Install interceptor drains
- * Install new pumping wells





MW 12-177 L1



Acknowledgements

- * SJRRPGW Development Team

- * Jon Traum (USGS), Primary Modeler
- * Steve Phillips (USGS), Project Manager
- * George Bennett (USGS), TPROGS Model Development
- * Celia Zamora (USGS) and Loren Metzger (USGS), Data Analysis

- * Other Acknowledgements

- * Katrina Harrison (USBR), USBR Project Manager
- * Claudia Faunt (USGS), Technical Guidance
- * Randy Hanson (USGS) and Wolfgang Schmid (University of Arizona), Code Development
- * Steven Predmore (USGS) and Donald Martin (USGS), Pre- and Post-Processing Tools
- * John Doherty (Watermark Numerical Computing), BeoPEST Developer
- * Susan Cundiff (Tetra Tech), Streamflow Rating Tables
- * Keith Halford (USGS) and Howard Reeves (USGS), Technical Review
- * Brian Heywood (CDM) and Bill Fernandez (CDM), Model Applications
- * Chris White (CCID) and Chris Montoya (DWR), Unpublished Data

Questions?

Preliminary Findings